



AR 460 bp C/F ø 32 BlueFlex™ cod. 32056



Technical specifications

AR Code	32056
Version	C/F ø 32
Diaphragms	6
Max flow (lpm)	450.3
Max flow (gpm)	119
Max Pressure (bar)	20
Max Pressure (psi)	290
Power (Hp)	22.4
RPM	550
Weight (Kg)	78.5
Size (mm) - L	566
Size (mm) - H	619
Size (mm) - W	500
Suction (mm)	ø 75
Outlet (mm)	ø 40
Max temperature (°C)	60



Product details

Semi-hydraulic six-diaphragm pump, for use in low pressure systems. Parts in contact with pumped liquids in plastic-coated aluminium Rilsan and AISI 303/304. Diaphragms in BlueFlex™. Seals in NBR. Fitted with air-hydraulic damper for smoother operation and less hammer effect in the delivery circuit. Die-cast casing with oil-immersed mechanism and clear plastic tank for visual level checking. Remote level monitoring sensor on request. Remote oil tank installation kit available on request. Pistons with ring for a more efficient "oil cushion" system to protect the diaphragm. New-design diaphragm cut-out system to prevent contact tearing even in heavy-duty operating conditions. Spherical sector profile valves for lower flow resistance and improved volumetric efficiency. Rugged feet secured to pump casing. Geomet stainless steel finish metal fasteners. Stopper for drainage of liquid from the circuit before storage over winter. Complete with drive shaft guard. Available kit for combining two pumps to form a modular unit to supply the sprayer's various uses.

Standard accessories



**Overpressure
valve cod. 1432**



**Universal shaft
guard for
constant
velocity P.T.O.
cod. 1492**

Optional accessories



**Closed guard
cod. 1482**



**Kit serbatoio
olio a distanza
cod. 42786**



**Kit camera aria
a distanza cod.
42868**