





**WARNING!**

SECTIONS  OF THE ASSEMBLY MARKED ARE NOT SHIELDED AND MUST BE SHIELDED BY AN INTERACTIVE GUARDING SYSTEM. BONDIOLI & PAVESI DECLINES RESPONSIBILITY IF PROPER GUARDS ARE NOT PROVIDED OR MAINTAINED.

**DANGER!**  
*Assembly supplied without external yoke.  
 Customer must install yoke complies with applicable standards.*

**PERICOLO!**  
*Trasmissione fornita senza forcella di estremità'.  
 Il cliente deve installare una forcella conforme alle normative di sicurezza.*

PROTEGGERE I PERNI CON I TAPPI E FORNIRE I 2 CUSCINETTI E I 2 SEEGER A PARTE

1	CODICE CODE	LATO TRATTORE TRACTOR SIDE	LATO MACCHINA IMPLEMENT SIDE	TIPO-TYPE	CLIENTE / CUSTOMER	RIF. CLIENTE / CUSTOMER REF.		
2	CODICE CODE 000			SFT-S8	3600502 Dani-Tech A/S			
3				DATA / DATE	DISEGNATO / DESIGNED BY	TIPO DI MACCHINA / TYPE OF IMPLEMENT		
4	 RILSAN L=1050	VELOCITA' MAX MAX SPEED	M max	13/5/2013	R. Moretti	STUDIO / DESIGN		ORIGINE / ORIGIN
		540 min <sup>-1</sup>	4000 Nm	LUNGHEZZA MAX IN LAVORO MAX WORKING LENGTH	LUNGHEZZA MAX TEMPORANEA MAX TEMPORARY LENGTH	NOTE / NOTES SPECIALE PER MANCANZA FORCELLA		
				LUNGHEZZA MAX NON IN ROTAZIONE MAX LENGTH AT STANDSTILL			CODICE / CODE DS8R121FXI001	REV. 0