



VITE TE.M16x2x120 c1.12.9
 COPPIA DI SERRAGGIO:
 314 Nm
 HEXAGON SCREW M16x2x120 c1.12.9
 TIGHTENING TORQUE:
 314 Nm

WARNING!
 SECTIONS OF THE ASSEMBLY MARKED ARE NOT SHIELDED AND MUST BE SHIELDED BY AN INTERACTIVE GUARDING SYSTEM. BONDIOLI & PAVESI DECLINES RESPONSIBILITY IF PROPER GUARDS ARE NOT PROVIDED OR MAINTAINED.

CENTRATURA SECONDO FIUT-07 GRADO 3
STRAIGHTENING ACCORDING TO FIUT-07 GRADO 3

1	CODICE CODE R94	LATO TRATTORE TRACTOR SIDE	LATO MACCHINA IMPLEMENT SIDE	TIPO-TYPE SFT-SK	CLIENTE / CUSTOMER 3600502 Dani-Tech A/S	RIF.CLIENTE / CUSTOMER REF.
* 2	CODICE CODE 5090K6501R			DATA / DATE 1/3/2017	DISEGNATO / DESIGNED BY A.Caffagni	
3	HEAT TREATED L=320			LUNGHEZZA MAX IN LAVORO MAX WORKING LENGTH Lw=667	TIPO DI MACCHINA / TYPE OF IMPLEMENT TRSKQ058001	
4	HEAT TREATED L=460	VELOCITA' MAX MAX SPEED 1325 min ⁻¹	M max 11000 Nm	LUNGHEZZA MAX TEMPORANEA MAX TEMPORARY LENGTH Lt=767	ORIGINE / ORIGIN DSKQ061FXR94001X	CODICE / CODE DSKQ058FXR94001X
				LUNGHEZZA MAX NON IN ROTAZIONE MAX LENGTH AT STANDSTILL Ls=773	NOTE / NOTES SPECIALE PER POS.2, LUNGHEZZA E CENTRATURA	REV. 0